

Calibrated Cobra Tie

- Quicker Selection of Corresponding Clamp with cable tie indicating bundle diameter at each point in the harness
- Visual Inspection of appropriate bundle diameter to prevent under or over tightening
- Long Lasting Indicator Marks laser engraving will not rub off like traditional hot stamp films
- Reduced Harness Snags during installation do to low profile head height
- No Sharp Tail Cutoffs remaining tail slips back into head leaving no exposed sharp edges
- Strong and Pure Quality manufactured from filtered nylon 6/6 reducing particle contamination and weak fracture points
- Available Materials Heat Stabilized Black or UV Black Nylon 6/6



Patent Pending

Per Bag	ACT Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	Per Case
100	MG-07-50-LP-CM-0-C	UV Black Nylon	7.5/190.5	.177/4.495	.053/1.346	50 lb.	1.75/44.45	10,000
1000	MG-07-50-LP-CM-0-M							
100	MG-07-50-LP-CM-30-C	Heat Stabilized Black Nylon	7.5/190.5	.177/4.495	.053/1.346	50 lb.	1.75/44.45	10,000
1000	MG-07-50-LP-CM-30-M							

Pawl support is required to obtain optimum tensile strength.
Tolerance: .xxx= +/- .005", .xx= +/- .015, Fraction= +/- 1/32"
Sold in case quantities

For Additional Information and Samples, Please Contact:

ACT Fastening Solutions
A Division Of Advanced Cable Ties, Inc.
245 Suffolk Lane
Gardner, MA 01440
800-861-7228

sales@actfs.com - www.actfs.com

ISO 9001:2000



008555

