

The Next Generation Of Cable Ties

- **Crosshatch Head Design** - patented feature strengthens strap pressure against locking mechanism
- **Safer** - rounded strap edges eliminates cuts, snags, and abrasions to cables, hoses, products, and users
- **Stronger** - high tensile strength achieved from deeper teeth in strap and one piece design
- **Faster** - low insertion and pull through force
- **Easier** - angled tail provides quicker initial insertion alignment and tail finger grips increases grasp for handling and tightening
- **Reliable** - manufactured with formulated molding processes, and filtered nylon, which reduces particle contamination



Standard 50 lb. Natural, UV Black, & Heat Stabilized

Per Bag	ACT Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	Per Case
500	AL-11-50-9-D	Natural	11.25/285.75	.180/4.572	.052/1.320	50 lb.	3.062/77.787	5,000
100	AL-11-50-9-C	Nylon						
500	AL-11-50-0-D	UV Black						
100	AL-11-50-0-C	Nylon						
500	AL-11-50-30-D	Heat Stabilized						
100	AL-11-50-30-C	Black Nylon						

Tolerance: .xxx = +/- .005, .xx = +/- .015, Fraction = +/- 1/32"

*Heat stabilized black ties have a 2 week lead time and are not Mil-Spec approved

Sold in case quantities

For Additional Information and Samples, Please Contact:

ACT Fastening Solutions
A Division Of Advanced Cable Ties, Inc.
245 Suffolk Lane
Gardner, MA 01440
800-861-7228



sales@actfs.com - www.actfs.com

ISO 9001:2000



00855